

BREAK SHARP CORNERS MAY BE EITHER CHAMFER OR RADIUS FROM 0.2 mm MIN. TO 1.0 mm MAX.

THIS DRAWING IS A SOLE PROPERTY OF M & M Ltd. IT SHOULD NOT BE REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT THEIR CONSENT

D

C

B

A

D


C

B

A

FOR PART DETAILS REFER DRAWING 007500026C91

REF PART NO:

UNSPECIFIED TOLERANCES AS PER ISO-2768-1:1989 (DIMENSION)										SURFACE FINISH SYMBOLS:ISO-1302						MAHINDRA & MAHINDRA LTD. FARM DIVISION, INDIA			
LINEAR IN mm.		OVER	0.5	3	6	30	120	400	1000	2000	WELDING SYMBOLS:IS813								
		UPTO	3	6	30	120	400	1000	2000	4000	REMOVE ALL SHARP CORNERS & BURRS								
f	FINE (X.XXX)		±0.05	±0.05	±0.1	±0.15	±0.2	±0.3	±0.5	-	DO NOT SCALE ALL DIMENSIONS ARE IN mm	<SC> COUNT : 0		NAME		DATE		PROJECT CODE: MSTAR	
m	MEDIUM (X.XX)		±0.1	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2	±2		<CC> COUNT : 0		DSNR	KRK	01-12-2023		ER NUMBER: ER23C0000252	
c	COARSE (X.X)		±0.2	±0.3	±0.5	±0.8	±1.2	±2	±3	±4		WEIGHT(kg) :		CHKR	NSP	01-12-2023		DESCRIPTION :	
v	VERY COARSE (X)			±0.5	±1	±1.5	±2.5	±4	±6	±8		S/F AREA(cm²): 0		APPR	KDS	01-12-2023		TOMMY BAR DIA 14 X 310	
ANGULAR IN deg.		LENGTH OF SHORTER SIDE OF THE ANGLE IN mm.										MATERIAL:							
		OVER	-		10		50		120										400
		UPTO	10		50		120		400		-								
f	FINE (X.XXX)		±1°		±0°30'		±0°20'		±0°10'		±0°5'								
m	MEDIUM (X.XX)						±0°30'		±0°15'		±0°10'								
c	COARSE (X.X)		±1°30'		±1°		±0°30'		±0°15'		±0°10'								
v	VERY COARSE (X)		±3°		±2°		±1°		±0°30'		±0°20'								
																PART NUMBER : 007601708D1		CL: NA	